Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-212-3575

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

### Shaft Diameter:

0.075 inches

#### Shaft Length:

0.050 inches

### **Body Length:**

0.250 inches

### Body Width:

0.175 inches

### **Body Height:**

### 0.250 inches

Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

# Center To Center Distance Between Terminals:

0.200 inches

# Lateral Distance Between Mounting Hole Centers:

0.200 inches

### **Terminal Location:**

Lower adjacent side single row

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

1.0 megohms single section

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.25 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section



### Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 pin

#### **Specification Data:**

81349-mil-r-22097/5 government specification

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0