

View Online at <https://aerobasegroup.com/nsn/5905-00-214-1363>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.500 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.469 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

140.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0