NSN 5905-00-214-2724

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-214-2724

view Offiline at https://aerobasegroup.com/nsi//0303-00-214-2/24
Section Quantity:
1
Body Style:
Cylindrical tab/flange mounted
Reliability Indicator:
Not established
Body Diameter:
0.785 inches
Mounting Hole Diameter:
0.136 inches
Body Length:
0.391 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.2 kilohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-214-2724

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0