## NSN 5905-00-215-4770

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-215-4770 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Body Length:** 0.532 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 100.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 295.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0 to 4.5 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and -1.5 to 1.5 85 degrees celsius single section and +0.0 to 3.5 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 

Unit Of Measure:

N/a

3 tab, solder lug Shelf Life:

## NSN 5905-00-215-4770

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A002a0