NSN 5905-00-215-4827

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-215-4827 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.5620 inches Pilot Length: 0.1320 inches **Overall Length:** 3.230 inches **Undercut Diameter:** 1.625 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.187 inches **Shaft Length:** 0.540 inches **Body Length:** 2.558 inches **Overall Diameter:** 1.750 inches **Mounting Lip Diameter:** 1.7500 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 11700.0 **Maximum Starting Torque:**

1.50 inch-ounces

Maximum Running Torque:

1.20 inch-ounces

Shaft End Play:

0.005 inches

NSN 5905-00-215-4827

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shaft Radial Play:
0.001 inches
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
11880.0
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-0.5 to 0.5 ohms single section
Resistance Tolerance Per Section In Percent:
-1.0 to 1.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
50000.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0