NSN 5905-00-216-6576

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-216-6576 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.229 inches **Body Width:** 0.582 inches **Body Height:** 0.769 inches **Shaft Bearing Type:** Bearing **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Fragility Factor:** Moderately rugged **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Printed circuit **Features Provided:** Humidity proof **Cubic Measure:** 0.102 cubic inches **Electrical Resistance Per Section:** 100.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 **Power Dissipation Rating Per Section In Watts:** 0.3 free air single section **Resistance Tolerance Per Section In Percent:** -30.0 to 30.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 solder stud

Shelf Life: N/a

NSN 5905-00-216-6576

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A002a0