Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-217-7960

# Section Quantity:

1

Body Style:

Rectangular w/bushing

**Reliability Indicator:** 

Not established

## Mounting Bushing Length:

0.250 inches

#### **Body Length:**

1.340 inches

#### **Body Width:**

0.440 inches

#### Body Height:

0.440 inches

#### Actuator Type:

Flush drive with slot-hole

#### Screw Thread Diameter:

0.216 inches

#### Screw Thread Series Designator:

Unf

#### Screw Thready Qty Per Inch (tpi):

28.0

### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

100.000 kilohms single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 0.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.7 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

### Standard Taper Curve Per Section:

A single section

#### **Terminal Type And Quantity:**

3 wire loop

# NSN 5905-00-217-7960

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0