Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-221-1043

### Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## Reliability Indicator:

Not established

### **Overall Length:**

0.415 inches

#### **Terminal Length:**

0.300 inches

### **Overall Height:**

0.375 inches

### Overall Width:

0.450 inches

#### Mounting Slot Width:

0.062 inches

#### Shaft Diameter:

0.040 inches

## Shaft Length:

0.060 inches

## Body Length:

0.375 inches

#### **Body Width:**

0.150 inches

#### **Body Height:**

0.375 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

7920.0

## Maximum Starting Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

0.200 inches

# Lateral Distance Between Mounting Hole Centers:

0.419 inches

## Mounting Facility Quantity:

2

### **Terminal Location:**

Left adjacent side single row



Mounting Method:
Unthreaded hole and terminal
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
500.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0