Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-221-4434

#### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.656 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.750 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

### 1.562 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms 1st section

# Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

# **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

# Standard Taper Curve Per Section:

A all sections

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0