

View Online at <https://aerobasegroup.com/nsn/5905-00-221-4458>

**Section Quantity:**

1

**Body Style:**

Cylindrical studs mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.188 inches

**Body Diameter:**

3.000 inches

**Mounting Hole Diameter:**

0.147 inches

**Shaft Diameter:**

0.375 inches

**Shaft Length:**

1.000 inches

**Body Length:**

1.188 inches

**Overall Diameter:**

3.000 inches

**Mounting Hole/stud Circle Diameter:**

0.875 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

300.0

**Maximum Starting Torque:**

4.00 inch-ounces

**Maximum Running Torque:**

3.00 inch-ounces

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

320.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

20.0 single section

**Special Features:**

3 mtg holes spaced 120 degrees apart on a 0.875 in. Radius 0.156 in. Diameter through hole in shaft includes tension spring

**Terminal Type And Quantity:**

3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0