NSN 5905-00-221-8111

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-221-8111

Section Quantity:
1
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
First Flat Length:
0.440 inches
Flat Height:
0.344 inches
Body Diameter:
5.090 inches
Shaft Diameter:
0.375 inches
Shaft Length:
0.870 inches
Body Length:
2.160 inches
Mounting Hole/stud Circle Diameter:
1.750 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
310.0
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
3.0 ohms single section
Rotary Actuator Travel In Angular Deg:

310.0

NSN 5905-00-221-8111

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 225.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab w/screw Shelf Life: N/a **Unit Of Measure: Demilitarization:** No