

View Online at <https://aerobasegroup.com/nsn/5905-00-221-9083>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.843 inches

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.312 inches

Overall Diameter:

1.515 inches

Shaft Style:

Round

Actuator Type:

Dual concentric

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Resistance Temperature Characteristic Range Per Section In Percent:

-0.0 to 3.0 -55 degrees celsius all sections and -5.0 to 10.0 -25 degrees celsius all sections and -5.0 to 10.0 25 degrees celsius all sections
and -0.0 to 3.0 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Test Data Document:

00752-373731 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0