Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-222-7650

Sec	ction	Qua	intity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

**Overall Length:** 

1.749 inches

Terminal Length:

1.500 inches

Body Diameter:

0.360 inches

Body Length:

### 0.249 inches

**Overall Diameter:** 

0.360 inches

### Actuator Type:

Flush drive with slot-hole

# Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Stop Torque:

10.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Rear end

### **Mounting Method:**

Terminal

**Electrical Resistance Per Section:** 

2.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

332.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# Power Dissipation Rating Per Section In Watts:

1.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## **Actuator Travel Control Feature:**

Stops



# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

### Fiig:

A002a0