

View Online at https://aerobasegroup.com/nsn/5905-00-222-8977

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.267 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.455 inches

Overall Diameter:

1.032 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.75 inch-ounces

Maximum Running Torque:

0.65 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Shaft End Play:

0.008 inches

Shaft Runout:

0.001 inches

Pilot Diameter Runout:

0.003 inches

Shaft Radial Play:

0.002 inches



Sc	crew Thread Diameter:
0.3	375 inches
Sc	crew Thread Series Designator:
Ur	nef
Sc	crew Thready Qty Per Inch (tpi):
32	2.0
Τe	erminal Location:
Lc	ongitudinally positioned on the circumference
M	ounting Method:
St	andard bushing
EI	ectrical Resistance Per Section:
5.	0 kilohms single section
R¢	otary Actuator Travel In Angular Deg:
36	600.0
Fι	unction Conformity Tolerance Per Section:
-0	.25/+0.25 single section
Aı	mbient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
10	05.0 single section
Te	empurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-7	0.0/+70.0 single section
Po	ower Dissipation Rating Per Section In Watts:
3.	0 free air single section
Fι	unction Conformity Per Section:
Si	ngle section independent linearity
Re	esistance Tolerance Per Section In Percent:
-1	0.0/+10.0 single section
A	ctuator Travel Control Feature:
St	ops
Fι	unction Characteristic Per Section:
Si	ngle section linear
Aı	mbient Tempurature In Deg Celsius Per Section At Full Rated Power:
40	0.0 single section
Τe	erminal Type And Quantity:
31	tab, solder lug
Sł	nelf Life:
N/	'a
Uı	nit Of Measure:
De	emilitarization:
No	0
Fi	ig:
A	002a0