## NSN 5905-00-223-3148

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-223-3148

Section Overtible
Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:  Not established
Body Diameter:  0.688 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.625 inches
Body Length:
0.328 inches
Overall Diameter:
0.766 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Tab
Electrical Resistance Per Section:
3.3 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:

A single section

## NSN 5905-00-223-3148

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0