

View Online at https://aerobasegroup.com/nsn/5905-00-225-0607

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.314 inches

Mounting Stud Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.500 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

9.00 inch-ounces

Maximum Stop Torque:

100.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.125 inches

Screw Thread Series Designator:

Unef



Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 1 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Threaded stud **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section 360 degrees sine Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -25.0/+25.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0