NSN 5905-00-225-8525

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-225-8525

One them Overwitten
Section Quantity:
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
0.188 inches
Body Length:
0.250 inches
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
15.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Switch Current Type And Rating In Amps:

1.500 ac

NSN 5905-00-225-8525

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0