## NSN 5905-00-225-8632

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-225-8632 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.875 inches **Body Diameter:** 1.313 inches **Shaft Diameter:** 0.251 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.550 inches **Body Length:** 1.375 inches **Overall Diameter:** 1.750 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 2.5 kilohms single section

**Terminal Type And Quantity:** 3 tab, solder lug

Shelf Life:

Onen Line

N/a

## NSN 5905-00-225-8632

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0