NSN 5905-00-225-8662

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-225-8662 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.252 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 2.440 inches **Overall Diameter:** 2.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:** 1.75 inch-ounces **Maximum Running Torque:** 1.25 inch-ounces **Maximum Stop Torque:** 1000.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches

0.002 inches

Shaft Runout:

NSN 5905-00-225-8662

Lateral Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.005 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
15.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
4.75 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
6 tab, solder lug

NSN 5905-00-225-8662

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0