NSN 5905-00-225-8881

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-225-8881 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Body Length:** 0.531 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 2.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** 295.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0 to 4.5 -55 degrees celsius single section and +0.0 to 2.5 -25 degrees celsius single section and -1.5 to 1.5 85 degrees celsius single section and +0.0 to 3.5 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section

Unit Of Measure:

N/a

Terminal Type And Quantity:

4 tab, solder lug Shelf Life:

NSN 5905-00-225-8881

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A002a0