NSN 5905-00-225-9939

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-225-9939 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3130 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.438 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.935 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.562 inches **Body Length:** 0.800 inches **Mounting Lip Diameter:** 1.9350 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Shaft End Play:** 0.004 inches

Shaft Runout: 0.001 inches

NSN 5905-00-225-9939

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
1.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
200.0 ohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
176.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0 to 400.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0 to 2.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-225-9939

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



_					
11	em)	 tor	172	n	

No

Fiig:

A002a0