NSN 5905-00-226-0582

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-226-0582
Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
Between 0.515 inches and 0.545 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
Between 0.362 inches and 0.405 inches
Mounting Hole Diameter:
Between 0.075 inches and 0.081 inches
Shaft Diameter:
0.050 inches
Shaft Length:
0.093 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.190 inches and 0.205 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
Between 0.190 inches and 0.210 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.515 inches and 0.530 inches
Mounting Facility Quantity:
2
Terminal Location:
Left adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
2.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-00-226-0582

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0