## NSN 5905-00-226-0914

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-226-0914 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.625 inches **Body Length:** 0.325 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** 0.535 in. Diameter body accommodation hole required **Terminal Type And Quantity:** 3 wire lead

Shelf Life:

N/a

## NSN 5905-00-226-0914

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0