NSN 5905-00-226-3587

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-226-3587

View Online at https://aerobasegroup.com/nsn/5905-00-22	? 6 -3
Section Quantity:	
1	
Body Style:	
Rectangular w/mounting holes/slots	
Reliability Indicator:	
Not established	
Overall Length:	
1.312 inches	
Terminal Length:	
Between 0.484 inches and 0.516 inches	
Overall Height:	
Between 0.780 inches and 0.844 inches	
Overall Width:	
Between 0.270 inches and 0.290 inches	
Mounting Hole Diameter:	
Between 0.083 inches and 0.093 inches	
Shaft Diameter:	
Between 0.109 inches and 0.141 inches	
Shaft Length:	
Between 0.046 inches and 0.078 inches	
Body Length:	
Between 1.234 inches and 1.266 inches	
Body Width:	
Between 0.270 inches and 0.290 inches	
Body Height:	
0.312 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
9000.0	
Maximum Starting Torque:	
5.00 inch-ounces	
Center To Center Distance Between Terminals:	
0.700 inches	
Lateral Distance Between Mounting Hole Centers:	
Between 0.995 inches and 1.005 inches	
Mounting Facility Quantity:	
2	
Torminal Lagations	

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-226-3587

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.000 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0