Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-226-6534

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# **Reliability Indicator:**

Not established

#### Mounting Hole Diameter:

0.073 inches

#### Shaft Diameter:

0.038 inches

- Shaft Length:
- 0.078 inches

Body Length:

#### 0.500 inches

Body Width:

#### 0.192 inches

**Body Height:** 

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Lateral Distance Between Mounting Hole Centers:

0.520 inches

#### **Mounting Facility Quantity:**

2

#### Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

500.000 ohms single section

## Rotary Actuator Travel In Angular Deg:

9000.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

## **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

# NSN 5905-00-226-6534

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0