NSN 5905-00-226-6535

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-226-6535

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.073 inches
Shaft Diameter:
0.038 inches
Shaft Length:
0.078 inches
Body Length:
0.500 inches
Body Width:
0.192 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
2.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section

NSN 5905-00-226-6535

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: