Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-226-9476

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

1.250 inches

#### **Body Diameter:**

1.156 inches

## Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

## Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

0.625 inches

## Overall Diameter:

1.750 inches

## Shaft Style:

Round

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

292.0

#### Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Running Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

192.00 inch-ounces

#### Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.531 inches

# Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# NSN 5905-00-226-9476

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.5 megohms single section **Rotary Actuator Travel In Angular Deg:** 312.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0 to 12.5 -55 degrees celsius single section and +0.0 to 6.2 -25 degrees celsius single section and +0.0 to 3.1 0 degrees celsius single section and +0.0 to 4.3 85 degrees celsius single section and +0.0 to 9.3 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 2.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** F single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0

---