Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-227-6989

## Section Quantity: 1 **Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.594 inches **Body Length:** 0.156 inches Actuator Type: Flush drive with slot-hole Effective Electrical Rotation In Deg Angular Rotation: 260.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Terminal **Electrical Resistance Per Section:** 250.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -30.0 to 30.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

## NSN 5905-00-227-6989

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

