

View Online at <https://aerobasegroup.com/nsn/5905-00-227-7065>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.1250 inches

**Overall Length:**

1.781 inches

**Undercut Diameter:**

1.860 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

2.000 inches

**Angle Of Mounting Hole In Deg:**

60.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.0

**Shaft Diameter:**

0.1875 inches

**Shaft Length:**

0.500 inches

**Body Length:**

1.250 inches

**Overall Diameter:**

2.203 inches

**Mounting Lip Diameter:**

2.0000 inches

**Mounting Lip Depth:**

0.9300 inches

**Mounting Hole/stud Circle Diameter:**

1.250 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

360.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

1.00 inch-ounces

**Shaft End Play:**

0.003 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.001 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.001 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thread Series Designator:**

Unc

**Screw Thread Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Threaded hole

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

16.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-1.0/+1.0 ohms single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Tap Location From Ccw Terminal Per Section In Ohms:**

8000.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Test Data Document:**

13499-381-0297 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0