

View Online at <https://aerobasegroup.com/nsn/5905-00-227-7065>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.1250 inches

Overall Length:

1.781 inches

Undercut Diameter:

1.860 inches

Undercut Width:

0.0620 inches

Body Diameter:

2.000 inches

Angle Of Mounting Hole In Deg:

60.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.1875 inches

Shaft Length:

0.500 inches

Body Length:

1.250 inches

Overall Diameter:

2.203 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.9300 inches

Mounting Hole/stud Circle Diameter:

1.250 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.003 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Threaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

16.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 ohms single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

8000.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Test Data Document:

13499-381-0297 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0