

View Online at <https://aerobasegroup.com/nsn/5905-00-228-5990>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Terminal Length:**

0.200 inches

**Body Diameter:**

0.450 inches

**Body Length:**

0.250 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

310.0

**Center To Center Distance Between Terminals:**

0.200 inches

**End Application:**

Los angeles class ssn (688); communications terminal, satellite an/gsc-3 (v)1; missile, all-weather antiship, harpoon (agm-84); ticonderoga class cg (47); sturgeon class ssn (637); support equipment, b-52 aircraft; helicopter, search and rescue, hh-60h; virginia class cgn (41) ; helicopter, carrier based asw, sh-60f; helicopter, uscg search and rescue, hh-60j

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Terminal

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

310.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0 to 70.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Stops

**Criticality Code Justification:**

Feat

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0