

View Online at <https://aerobasegroup.com/nsn/5905-00-228-5990>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.200 inches

Body Diameter:

0.450 inches

Body Length:

0.250 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

310.0

Center To Center Distance Between Terminals:

0.200 inches

End Application:

Los angeles class ssn (688); communications terminal, satellite an/gsc-3 (v)1; missile, all-weather antiship, harpoon (agm-84); ticonderoga class cg (47); sturgeon class ssn (637); support equipment, b-52 aircraft; helicopter, search and rescue, hh-60h; virginia class cgn (41) ; helicopter, carrier based asw, sh-60f; helicopter, uscg search and rescue, hh-60j

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

310.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Feat

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0