NSN 5905-00-228-6902

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-228-6902 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.656 inches **Body Diameter:** 0.781 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.295 inches **Body Length:** 0.406 inches **Overall Diameter:** 0.940 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Radius:** 0.375 inches **Shaft Runout:** 0.002 inches **Shaft Radial Play:** 0.002 inches **Screw Thread Diameter:** 0.500 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

250.0 kilohms single section

NSN 5905-00-228-6902

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 0.2 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A002a0