## NSN 5905-00-228-6961

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-228-6961

Electrical Resistance: 3.400 kiohms Resistance Tolerance In Percent: -0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.105 inches Body Diameter: 0.028 inches Power Dissipation Rating In Watts: 0.028 inches Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (fils is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -0.1004-0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -0.000 inches Body Diameter: -0.105 inches Body Diameter: -0.105 inches Body Length: -0.281 inches Power Dissipation Rating in Watts: -0.092 cubic inches Style Designator:	-15.0/+15.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.058 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure:	Electrical Resistance:
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 004841-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	3.400 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length: 2.000 inches  Body Diameter: 0.105 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  ———————————————————————————————————	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-0.100/+0.100
Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length: 2.000 inches  Body Diameter: 0.105 inches  Body Diameter: 0.281 inches  Power Dissipation Rating in Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	125.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Nota Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.056 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	145.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Method:
Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.105 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Test Data Document: 00481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Flig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Terminal Type:
Note stablished Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Terminal Length:  2.000 inches  Body Diameter:  0.105 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.050 free air  Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Reliability Indicator:
2.000 inches  Body Diameter: 0.105 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Diameter:  0.105 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Terminal Length:
0.105 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	2.000 inches
Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.050 free air  Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
0.281 inches  Power Dissipation Rating In Watts: 0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.105 inches
Power Dissipation Rating In Watts:  0.050 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Length:
Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.281 inches
Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Style Designator:  Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.050 free air
Style Designator:  Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Cubic Measure (non-core):
Axial terminal each end  Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.002 cubic inches
Test Data Document:  06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0