Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-229-0297

#### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.555 inches

#### Body Diameter:

1.640 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

1.680 inches

#### **Overall Diameter:**

2.040 inches

### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

## Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

3.5 kilohms all sections

# Power Dissipation Rating Per Section In Watts:

2.0 free air all sections



#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

## Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0