## NSN 5905-00-229-1778

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-229-1778

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.312 inches
Body Diameter:
0.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.062 inches
Mounting Bushing Length:
0.090 inches
Body Length:
0.250 inches
Overall Diameter:
0.500 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 kilohms single section
Power Dissipation Rating Per Section In Watts:

3.0 free air single section

## NSN 5905-00-229-1778

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	ln	Percent:
------------	-----------	-----	---------	----	----------

-15.0/+15.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0