## NSN 5905-00-229-2272

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-229-2272

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.320 inches
Overall Height:
0.315 inches
Overall Width:
0.190 inches
Mounting Hole Diameter:
0.093 inches
Shaft Length:
0.080 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.315 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
0.10 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Left adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175 0 single section

175.0 single section

## NSN 5905-00-229-2272

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0