

View Online at <https://aerobasegroup.com/nsn/5905-00-229-7359>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.6250 inches

Pilot Length:

0.0620 inches

Overall Length:

3.447 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.880 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

0.500 inches

Body Length:

2.916 inches

Overall Diameter:

1.065 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0 and 3595.0

Maximum Starting Torque:

1.20 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.0015 inches

Shaft Radial Play:

0.0015 inches

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

50.0 kilohms all sections

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

2635.0 1st section

Rotary Actuator Travel In Angular Deg:

3602.0 and 3607.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 all sections

Tap Location Tolerance Per Section:

-1.0/+1.0 ohms all sections

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Crgd

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 all sections

Test Data Document:

18876-10243516 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0