

View Online at <https://aerobasegroup.com/nsn/5905-00-230-7631>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.344 inches

Body Diameter:

0.938 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.875 inches

Mounting Bushing Length:

1.000 inches

Body Length:

0.469 inches

Overall Diameter:

1.562 inches

Undercut Diameter:

0.250 inches

Shaft Style:

Round, stepped, knurled

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Undercut Length:

0.250 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 heat sink single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0