## NSN 5905-00-230-8582

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-230-8582 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.785 inches **Body Length:** 0.642 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method: Terminal Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5905-00-230-8582

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A002a0