NSN 5905-00-230-8696

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-230-8696

Ocation Occupation
Section Quantity:
Body Style:
Cylindrical Pallatellita Indicators
Reliability Indicator:
Not established
Overall Length: 0.415 inches
Body Diameter: 0.594 inches
Body Length:
0.219 inches
Overall Diameter:
0.875 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
0.75 inch-ounces
Maximum Stop Torque: 48.00 inch-ounces
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
1.0 kilohms single section Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops Stops
Stops

NSN 5905-00-230-8696

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0