## NSN 5905-00-230-8698

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-230-8698

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.415 inches
Body Diameter:
0.594 inches
Body Length:
0.219 inches
Overall Diameter:
0.875 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
0.75 inch-ounces
Maximum Stop Torque:
48.00 inch-ounces
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops

## NSN 5905-00-230-8698

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Power:



Ambient Tempurature In Deg Celsius Per Section At Full Rated
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/o

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A002a0