## NSN 5905-00-231-3641

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-231-3641

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -500.0 to 200.0  Electrical Resistance: 1.450 megohms  Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established
Electrical Resistance:  1.450 megohms  Resistance Tolerance In Percent:  -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 150.0  Inclosure Method:  Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established
1.450 megohms  Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established
Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
-1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Hermetically sealed Teminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
-55.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
-55.0 to 150.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established
Terminal Type: Wire lead Reliability Indicator: Not established
Wire lead  Reliability Indicator:  Not established
Reliability Indicator: Not established
Not established
Torminal Laureth
Terminal Length:
1.500 inches
Body Diameter:
0.250 inches
Body Length:
0.750 inches
Power Dissipation Rating In Watts:
0.500 free air
Style Designator:
Axial terminal each end
Test Data Document:
18874-9158136 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A001a0