Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-232-1824

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9688 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.625 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.761 inches

Shaft Diameter:

0.1247 inches

Shaft Length:

2.656 inches

Body Length:

2.031 inches

Mounting Lip Diameter:

1.7500 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

2.10 inch-ounces

Maximum Running Torque:

2.10 inch-ounces

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference



Mounting	Mashad	
Mounting		
Clamp ring		
Humidity p		
	Resistance Per Section:	
•	rcent, rated amperes c and better finish	
	tuator Travel In Angular Deg:	
360.0		
	Conformity Tolerance Per Section:	
	0.0025 1st section	
	Fempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 all s		
	ssipation Rating Per Section In Watts:	
	condary finish	
	Conformity Per Section:	
	s absolute conformity	
	e Tolerance Per Section In Percent:	
-5.0/+5.0 1		
	Travel Control Feature:	
Continuous		
	Characteristic Per Section:	
All sections		
	ure Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:	
	00.0 3rd section	
Ambient T	Fempurature In Deg Celsius Per Section At Full Rated Power:	
85.0 all se	ctions	
Test Data	Document:	
	32039 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, e	etc.;
excludes a	any specification, standard or other document that may be referenced in a basic governing drawing)	
Terminal 7	Type And Quantity:	
11 turret		
Shelf Life:		
N/a		
Unit Of Me	easure:	
Demilitari	zation:	
No		
Fiig:		
A002a0		