## NSN 5905-00-232-3462

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-232-3462

Electrical Resistance: 37.300 kilohms Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1175.0 Interpurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Incapsulated Interpurature Range Of Tempurature Celsius: Interpurature Range Of Tempurature Celsius: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Tempurature Celsius At Zero Percent Rated Power: Interpurature Range Of Temp
Resistance Tolerance In Percent:  0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:
Resistance Tolerance In Percent:  0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:  0.250 free air
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.025 inches  Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.001  Body Diameter:  1.188 inches  Body Length:  1.0625 inches  Power Dissipation Rating In Watts:  1.250 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Incapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  10.001  Body Diameter:  10.188 inches  Body Length:  10.625 inches  Power Dissipation Rating In Watts:  10.250 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  10.001  Body Diameter:  10.188 inches  Body Length:  10.625 inches  Power Dissipation Rating In Watts:  10.250 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.188 inches Body Length: 0.625 inches  Power Dissipation Rating In Watts: 0.250 free air
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.250 free air
Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:
Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches  Body Length:  0.625 inches  Power Dissipation Rating In Watts:  0.250 free air
20.001  Body Diameter: 20.188 inches  Body Length: 20.625 inches  Power Dissipation Rating In Watts: 20.250 free air
Body Diameter:  0.188 inches  Body Length: 0.625 inches  Power Dissipation Rating In Watts: 0.250 free air
0.188 inches  Body Length: 0.625 inches  Power Dissipation Rating In Watts: 0.250 free air
Body Length:  0.625 inches  Power Dissipation Rating In Watts:  0.250 free air
0.625 inches  Power Dissipation Rating In Watts: 0.250 free air
Power Dissipation Rating In Watts: 0.250 free air
0.250 free air
Style Designator:
· · · · · ·
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0