NSN 5905-00-232-3639

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-232-3639

Section Quantity:
1
Body Style:
Rectangular w/mounting hole/slot
Reliability Indicator:
Not established
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.375 inches
Body Width:
0.145 inches
Body Height:
0.390 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
5.00 men dances
Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals:
Center To Center Distance Between Terminals: 0.200 inches
Center To Center Distance Between Terminals: 0.200 inches Terminal Location:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 500.0 ohms single section
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 500.0 ohms single section Rotary Actuator Travel In Angular Deg:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 500.0 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 500.0 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal:
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 500.0 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches
Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Rear end Mounting Method: Terminal Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 500.0 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

1.0 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-232-3639

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31413-230269 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Ferminal Type And Quantity:
3 pin
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization: