## NSN 5905-00-232-4500

-100.0/+100.0

**Electrical Resistance:** 

Inductive Wire Wound Fixed Resistor - Page 1 of 2

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 



View Online at https://aerobasegroup.com/nsn/5905-00-232-4500

| 0.681 ohms   |
|--|
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+275.0   |
| Inclosure Method:  |
| Encased  |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length:   |
| 0.312 inches   |
| Body Length:   |
| 0.750 inches   |
| Body Width:  |
| 0.438 inches   |
| Body Height:   |
| 0.406 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:   |
| 0.562 inches   |
| Power Dissipation Rating In Watts:   |
| 6.000 free air   |
| Mounting Hole Size:  |
| 0.094 inches   |
| Style Designator:  |
| Axial terminal (s)   |
| Test Data Document:  |
| 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39009/1 government specification   |
| Shelf Life:  |
| N/a  |

## NSN 5905-00-232-4500

Inductive Wire Wound Fixed Resistor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A001a0