## NSN 5905-00-232-4503

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-232-4503

Electrical Resistance: 31.900 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches Body Length:
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.001 Body Diameter:  0.188 inches
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0 nclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.001 Body Diameter:  0.188 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  10.001  Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  nclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  nclosure Method: Encapsulated Ferminal Type:  Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches
Encapsulated  Ferminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.188 inches
Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter: 0.188 inches
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.188 inches
Established Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches
Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.188 inches
0.001  Body Diameter: 0.188 inches
Body Diameter: 0.188 inches
0.188 inches
3ody Length:
0.625 inches
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0