

View Online at https://aerobasegroup.com/nsn/5905-00-232-8089

# Section Quantity:

2

# Body Style:

Cylindrical servo mounted

## **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

Between 0.7495 inches and 0.7500 inches

#### **Pilot Length:**

0.0620 inches

#### **Overall Length:**

1.374 inches

#### **Undercut Diameter:**

0.750 inches

#### **Undercut Width:**

## 0.0570 inches

**Body Diameter:** 

0.875 inches

#### Shaft Diameter:

Between 0.1245 inches and 0.1250 inches

#### Shaft Length:

Between 0.230 inches and 0.270 inches

#### **Body Length:**

1.174 inches

#### **Overall Diameter:**

1.250 inches

#### Mounting Lip Diameter:

0.8750 inches

#### Mounting Lip Depth:

0.0620 inches

## Shaft Style:

Round

## Shaft Bearing Type:

Bearing

# Actuator Type:

Double ended shaft

# Effective Electrical Rotation In Deg Angular Rotation:

Between 336.6 and 343.4

# Maximum Starting Torque:

0.50 inch-ounces

## Maximum Running Torque:

0.55 inch-ounces



# Shaft End Play: 0.0045 inches Shaft Runout: 0.001 inches Lateral Runout: 0.002 inches **Pilot Diameter Runout:** 0.001 inches Shaft Radial Play: 0.001 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 2.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.25 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 100.0 all sections **Terminal Type And Quantity:** 6 turret Shelf Life:

N/a



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0