## NSN 5905-00-232-8462

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-232-8462

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.9370 inches
Pilot Length:
0.0310 inches
Undercut Diameter:
1.937 inches
Undercut Width:
0.0800 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Body Length:
1.031 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0800 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:

Clamp ring

## NSN 5905-00-232-8462

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
0.80/+0.80 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
35.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
2.0/+2.0 ohms single section
Resistance Tolerance Per Section In Percent:
1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
25.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
54.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0